
User Manual

Cable Connection

For Q5L+Q5L



Contents

1. Toggle Switch Setup 1
    1.1. Where to find the toggle (DIP) switches? 1
    1.2. Set the toggle switch 1
    1.3. Problem from Toggle switch setup incorrectly 1
2. Dashboard Removal 2
3. Cable Connection 3
    3.1. Cable Connection Chart 3
    3.2. Power Cable Connection 4
    3.3. A/C Controller Power Cable Connection 5
    3.4. LVDS Cable Connection 6
    3.5. WiFi Antenna and USB-AV Cable Connection 7
    3.6. FPC Adapter Board Connection 8
    3.7. AMI Audio Cable Connection 9
    3.8. Microphone Connection 10
    3.9. Where to Put the CarPlay Box? 11
4. CarPlay Sound Setup 11
    4.1. AUX or AMI Output 12
    4.2. Phone Bluetooth Output 14
5. Reverse and Front Cameras 16
    5.1. Original OEM Camera 16
    5.2. After Market Camera 17
    5.3. Front View Cameras 19
6. FAQ 20
7. Contact US 21

1. Toggle Switch Setup


1.1 Where to find the toggle（DIP）switches?




1.2 Set the toggle switch

for Audi A4 A5 Q5 with Concert or Symphony radio

dial setup



Smart Link System



	1	2	3	4	5	6	7	8
Off								
On				✓		✓		✓

Pin 7: with OEM parking sensor → Off / 0, No OEM parking sensor → On /1

Tips:

Pin 7: with OEM parking sensor → Off / 0, No OEM parking sensor → On /1

1.3 Toggle switch setup incorrectly will result in a black screen, flash screen, half-screen, etc.

Please contact us for the correct toggle switch setup code if you meet problems as in the follow chart.

Black screen when switch to CarPlay function	Flash screen in OEM function
	
Half-screen when switch to CarPlay function	Half-screen when switch to CarPlay function
	


2. Dashboard Removal

Please scan QR code, view the detail via YouTube video on dashboard removal guidance.

For A4 A5 Q5

3. Cable Connection


3.1 Cable connection chart



Please follow the connection chart accurately (detailed instructions below).


After the cables are all connected, you will be able to switch between the original Audi and the CarPlay interfaces by long pressing the “MEDIA” button or “CAR” button on the MMI controller. or “NAV” button from the steering wheel control.






3.2 Head Unit power cable connection

Unplug the OEM original power cable from the head unit and reconnect it to the new cable harness. Then plug the new cable into the head unit.



Note: In the power cable, don't need to connect the gray cable to the green cable.



3.3 A/C controller power cable connection







3.4 LVDS cable connection

1) New LVDS cable 1 goes to the LVDS port of OEM the head unit.
2) New LVDS cable 2 goes to the original LVDS cable.


Note: Connecting the LVDS cables incorrectly will result in a black screen!



3.5 WiFi antenna and USB-AV cable connection




Note: To avoid losing the WiFi signal, make sure the antenna is not placed close to metal objects.



3.6 FPC adapter board installation

Before install the FPC adapter board, you need to test the CarPlay function. Below are the correct steps for FPC adapter board installation. (Please do them step by step)

Step 1: set the correct toggle switch.
Step 2: install all the cable, including the head unit power cable, the A/C controller power cable, the headlight range control cable, the LVDS cable and the WiFi antenna.
Step 3: start the car engine, open the iPhone WiFi and Bluetooth, search and pair the "CarPlay83****" Bluetooth, then check whether the screen show the CarPlay system
Step 4: If the Step 3 is successful, power off the car engine, start to install the FPC adapter board according the pictures and video instruction below.



Please scan QR code, view the detail via YouTube video on the FPC adapter board installation.


3.7 AMI audio cable connection (only for Audi cars with AMI function)

If your car has AMI port, you need to connect the AMI cable to your car AMI port, so that the sound from the CarPlay function will work via the car's AMI AUX function.

Where to find the AMI port?

in the glove-box	in the glove-box
	
in the central console box	**behind media interface doors**
	

AMI cable connection



3.8 Microphone connection



Aftermarket mic should be installed close to the driver position.



3.9 Where to put the CarPlay box?

The CarPlay interface decoder box should be installed in an appropriate space near, or on, the OEM head unit. Or in the glove box.

on the OEM head unit	Beside the OEM head unit
	
In the glove box box	In the glove box box
	

4. CarPlay Decoder Sound Setup

Two ways optional for sound transmission to car audio: AUX output and phone Bluetooth output.

4.1 AUX or AMI output

4.1.1 If your phone already has a bluetooth connection to your car, disconnect it.

4.1.2 Set the AUX


Before using the CarPlay system, you need to set the sound input on your OEM interface to "AUX", otherwise the CarPlay /Android Auto system will have sound!

On the original Audi System, navigate to the "Media" interface, click the "External audio input"




4.1.3 Set AMI (only for Audi cars with AMI function)

If your car has AMI port, after connect the AMI cable to your car AMI port, you need to set the "Media" into "AMI"




After the cables are all connected, you will be able to switch between the original Audi and the CarPlay interfaces by long pressing the “MEDIA” button or “CAR” button on the MMI controller. or “NAV” button from the steering wheel control.





The CarPlay decoder main interface







4.2 Phone Bluetooth output

Note: This sound connection mode only supports Carplay and Android Auto, as well as Bluetooth calls. USB/SD card music video sound output is not supported. Mirrored sound output is not supported.

4.2.1 Set the CarPlay decoder box sound output mode into “Use Car’s BT Channel”

Enter the “Setup” menu from the decoder main menu , Set the “Audio output channel” into “Use Car’s BT Channel” .


Step 1	Step 2
	
Step 3	**Step 4**
	

4.2.2 Pair the Phone Bluetooth to the OEM Audi Bluetooth


4.2.3 After the phone Bluetooth is paired successfully, Keep the original OEM Audi system into Bluetooth audio page, and long pressing the “MEDIA” button or “CAR” button on the MMI controller, or “NAV” button from the steering wheel control to enter into the CarPlay decoder interface and enjoy the CarPlay/Android auto.







The CarPlay decoder main interface



5. Reverse and Front Cameras


5.1 Original OEM camera

Setting is different for the Automatic Transmission car and the Manual Transmission car.

5.1.1 Setup for Automatic Transmission car with original OEM camera


Enter the “Setup” menu from the decoder main menu, choose “Reverse”, then make sure the “Reverse Camera” option is set to “Original”.

Make sure that the following three options are all set to “off”.




5.1.2 Setup for Manual Transmission car with original OEM camera

Enter the “Setup” menu from the decoder main menu, choose “Reverse”, then make sure the “Reverse Camera” option is set to “Original”, and set the “Reverse line detect” into “on”, the others are set to “off”



After set the “Reverse line detect” into “on”, for the Manual Transmission car, you need to connect the “Back/Reverse detect” wire to your car reverse lamp positive (+12V).

You manage to get a wire long enough to connect it (connect the Reverse detect wire to your car reverse lamp +12V), because it doesn’t come with the package.




5.2 Aftermarket reverse camera


Setting is different for the Automatic Transmission car and the Manual Transmission car.

5.2.1 Setup for Automatic Transmission car with aftermarket camera

Enter the “Setup” menu from the decoder main menu, choose “Reverse”, then make sure the “Reverse Camera” option is set to “Aftermarket”.

Make sure that the following three options are all set to “off”.







Aftermarket rear view camera cable connection for Automatic Transmission car

5.2.2 Setup for Manual Transmission car with aftermarket camera

Enter the “Setup” menu from the decoder main menu, choose “Reverse”, then make sure the “Reverse Camera” option is set to “Aftermarket”, and set the “Reverse line detect” into “on”, the others are set to “off”







Aftermarket rear view camera cable connection for Manual Transmission car

5.3 Front view cameras

Front view camera settings: enter into the “Reverse” setting interface, and set the front view time between 1 to 15 seconds.



Tip: if your car doesn’t install the front view camera, please set the front view time into 0 seconds.



Front view camera cable connection


6 FAQ

1. Why is there no sound during CarPlay function?

Solution: Check the car, if the car has AMI port, AMI cable needs to be connected to the original AMI port.

2. How do I activate Siri?

There are two ways to activate the Siri function:
1) Use the Voice Control button on the steering wheel or
2) Long press the confirm button on the iDrive controller





7 Contact Us

Please contact us via purchase platform, mail or the WhatsApp if you need any help.

Tip:
before contacting us, please help us to collect the following information.

1. the order ID
2. the car model
3. the year of the car
4. screen size of the car
5. the toggle switch setup
6. pictures about the LVDS cable connection
7. the software version (in the CarPlay decoder menu, enter into the “Setting”, choose the “System Version”, you will see the software version.)

